

May 1st, 1958.

	<u>Export</u>	<u>Basic</u>	<u>Total</u>
EXAKTA VAREX 11A, with standard reflex finder.			
Without lens	46. 3. 7	69. 5. 4	82.15. 6
Fitted with:			
58mm f2 Biotar	87.12. 1	131. 8. 2	157. 0. 8
50mm f2.8 Tessar	74.13. 1	111.19. 8	133.16. 4
58mm f1.9 Primoplan	68.12. 3	102.18. 5	122.19. 9
Hide Ever Ready Case	2.18. 0	3.12. 9	4. 6.11
Leather lanyard for Varex & Exa.	18.11	1. 3. 6	1. 8. 1
STANDARD REFLEX FINDER with Ground Glass Screen	4.18. 6	7. 7. 9	8.16. 7
PENTA PRISM (for Varex 11a and Exa) fitted with standard ground glass screen.	12. 1. 8	18. 2. 6	21.13. 2
Case for above	12. 1	18. 2	1. 1. 8
Eye Piece for Penta Prism (rotating)	1.11. 0	2. 6. 6	2.15. 6
EXPOSURE METER ACCESSORY	21.12. 0	32. 8. 0	38.14. 4

LENSES.

STANDARD FOCAL LENGTH.

50mm f2.8 Tessar	A.P.D.	28. 9. 9	42.14. 8	51. 1. 3
58mm f2 Biotar	A.P.D.	41. 8. 5	62. 2. 9	74. 5. 1
58mm f1.9 Primoplan	P.D.	22. 8.11	33.13. 5	40. 4. 9

WIDE ANGLE

35mm f2.8 Flektogon	A.P.D.	45. 6. 3	67.19. 5	81. 4. 0
35mm f4.5 Primoplan	P.D.	15.10. 9	23. 6. 1	27.17. 0

LONG FOCUS AND TELEPHOTO

75mm f1.5 Biotar	P.D.	60.11. 9	90.17. 8	108.12. 1
80mm f2.8 Biometar	P.D.	31.17. 0	47.15. 5	57. 1. 9
100mm f2.8 Trioplan	A.P.D.	26.15. 1	40. 2. 8	47.19. 2
100mm f2.8 Trioplan	P.D.	20.14. 3	31. 1. 5	37. 2. 7
135mm f4 Triotar	P.D.	28. 9. 9	42.14. 8	51. 1. 3
135mm f3.5 Primotar	P.D.	23. 6. 0	34.19. 0	41.15. 4
180mm f5.5 TeleMegor	P.D.	26.15. 1	40. 2. 8	47.19. 2
180mm f3.5 Primotar	P.D.	30. 9. 5	45.14. 1	54.12. 4
180mm f2.8 Sonnar	P.D.	81.19.11	122.19.10	146.19. 8
300mm f4.5 TeleMegor	P.D.	52. 5. 3	78. 7.10	93.13. 8
300mm f4 Sonnar	P.D.	104.15. 8	157. 3. 6	187.16. 6
400mm f5.5 TeleMegor	P.D.	49.12. 8	74. 9. 0	88.19. 4
500mm f8 Zeiss Distance Lens		107.13. 3	161. 9.11	192.19. 9
Screw-in Light Yellow filter for above.		8. 9. 2	12.13. 9	15. 3. 3
Tellup Magnifier lens in case.		2.17. 0	4. 5. 5	5. 1. 4

Hide Cases for:

35mm f2.8 Flektogon		2. 3. 1	2.13. 6	3. 3.11
100mm f2.8 Trioplan		1.12.10	2. 0. 9	2. 8. 9
135mm f4 Triotar		2. 9. 2	3. 1. 0	3.12.11
500mm Zeiss Distance Lens		5.19. 1	8.18. 7	10.13. 4

EXA with Standard Reflex Finder.

Fitted with:

50mm f2.9 Meritar	P.D.	24.18. 1	37. 7. 1	44.12. 7
50mm f2.9 Trioplan		28. 3. 9	42. 5. 7	50.10. 5
50mm f2.8 Tessar		33.15.10	50.13. 9	60.11. 5
Hide Ever Ready Case for EXA		2.11. 9	3. 4. 3	3.16. 9

Interchangeable Focusing Screens for PENTA  
PRISM AND SCIENTIFIC VIEW FINDER (MAGNEAR)

Standard Ground Glass Screen	1. 4. 2	1.16. 3	2. 3. 4
Standard Ground Glass Screen incorporating Hair Line Cross	2. 0. 6	3. 0. 9	3.12. 7
Clear Centre Spot	3. 3.10	4.15. 9	5.14. 5
Clear Centre Spot and Hairline Cross	4. 4. 7	6. 6.11	7.11. 7
1/16th inch divisions	7.17. 1	11.15. 8	14. 1. 7
1/8th inch divisions	6. 4. 3	9. 6. 5	11. 2. 9
Millimetre divisions	6. 4. 3	9. 6. 5	11. 2. 9
Overall 5mm square divisions	4. 6. 5	6. 9. 8	7.14.11
Zeiss Distance Meter	9. 1. 3	13.11.11	16. 4.11
Clear Glass with Hairline Cross	2.14. 5	4. 1. 7	4.17. 6
Clear Glass with Hairline Cross and mm divisions	6.15. 7	10. 3. 4	12. 2.11

Interchangeable Focusing Screens for STANDARD  
REFLEX FINDER

Standard Ground Glass Screen	1.14. 8	2.12. 0	3. 2. 2
Standard Ground Glass Screen incorporating Hair Line Cross	2.18. 8	4. 7.11	5. 5. 1
Clear Centre Spot	2.18. 8	4. 7.11	5. 5. 1
Clear Centre Spot and Hairline Cross	3.19. 4	5.19. 0	7. 2. 2
1/16th inch divisions	8.12. 7	12.18.11	15.14. 5
1/8th inch divisions	6.19. 9	10. 9. 8	12.10. 6
Millimetre divisions	6.19. 9	10. 9. 8	12.10. 6
Overall 5mm square divisions	4.16. 8	7. 5. 0	8.13. 3
Clear Glass	2. 6. 7	3. 9.10	4. 3. 5
Clear Glass with Hairline Cross	3. 2. 3	4.13. 5	5.11. 5

LENS MAGNIFIER (MAGNEAR)

with Standard Focusing Screen (for special  
purpose screens please see Interchangeable  
Screens for Penta Prism and Magnear)

Top Lens Magnifier	4. 6. 5	6. 9. 8	7.14.11
	3. 9. 1	5. 3. 7	6. 3. 9

KOLPOFOT

Complete	143. 0. 0	187. 0. 0	187. 0. 0
----------	-----------	-----------	-----------

Unit comprises:

Bellows focusing attachment with slide rail, and flash head bracket.		28. 0. 0	28. 0. 0
---	--	----------	----------

135mm f4 Zeiss Triotar lens, with aperture ring calibrated to f45		48. 0. 0	48. 0. 0
--	--	----------	----------

Blohm Central Electronic Flash Unit ZB3 with Pilot Light and two connecting cables.		56. 0. 0	56. 0. 0
--	--	----------	----------

Ihagee/Langham Power Pack with switch 100/200 joules output dual neon indicators finger tip control panel and inbuilt transformer for pilot light.		55. 0. 0	55. 0. 0
---	--	----------	----------

Special pattern flash head with standard reflector complete with Mazda FA9 Flash tube (200 joules)			
---	--	--	--

for use in conjunction with Ihagee/Langham power pack. Optional extra.		18.18. 0	18.18. 0
---	--	----------	----------

VIELZWECK

Universal Copying Equipment, complete with all accessories.

Unit comprises:

Baseboard with column head, two extension columns, stop rings and pegs

Slide rail

Bellows focusing attachment

Transparency copying device, with light baffle

EXAKTA camera cradle with rotating head, and angular connecting bracket

Tripod base for above

43.13. 6	65.10. 1	78. 5. 8
13. 5.10	19.18. 9	23.16. 6
7. 1. 7	10.12. 4	12.13. 9
9. 9.11	14. 4.10	17. 0. 4
7. 5.10	10.18. 9	13. 1. 5
5. 6. 2	7.19. 2	12.17. 5
1. 4. 2	1.16. 3	1.17. 6

STEREOSCOPIC EQUIPMENT

Zeiss Prismatic Stereo attachment. 65mm base focusing range 2 metres to infinity

Zeiss Prismatic Stereo attachment 12mm base focusing range 2 metres to 0.2 metres

Stereflex twin-ocular focusing and viewing device

Reducing ring for attaching 65mm base unit to 50mm f3.5 Tessar or 50mm f2.8 Tessar lenses (without P.D. or A.P.D.)

Proxar lenses for Stereo Attachment with 12mm base. 20cm. 30cm. 50cm. each

32. 8. 4	48.12. 5	58. 2. 0
24.13.10	37. 0. 9	44. 5. 2
16. 8. 1	24.12. 2	29. 8. 2
1. 0. 9	1.11. 1	1.17. 2
2.15. 2	4. 2. 9	4.18.10

EXAKTA FLASH GUN. (Capacitor Type) complete with 6" Reflector, connecting lead to camera

9.16. 0	12. 3. 3	14.10. 8
---------	----------	----------

SUNDRY ACCESSORIES

Extension Tubes and Adapter Rings, comprising three Tubes (5, 10 and 30mm). Adapter Rings used without tubes, 10mm. In plated brass

As above, in Aluminium

Two-in-one Ring 5mm

MICROSCOPE ATTACHMENT, Type 11, Bayonet

Plated Brass

MICROSCOPE ATTACHMENT, Type 1, Hinged,

Aluminium

32mm, 42mm and 51mm Reversal Rings, allowing use of the camera lens in reversed position for extreme near distance focusing, with scale of reproduction exceeding 1 : 1

Rear bayonet Adapter Ring (to accept Reversal Ring)

Camera body cap

Rear lens bayonet cap

Lens caps. 32mm. 37mm. 42mm.

51mm. 60mm.

Lens hood (slip-on) 32mm. 37mm. 42mm.

Giant release button

4. 6. 5	6. 9. 8	7.14.10
3. 5. 8	4.18. 6	5.17. 8
2. 4.11	3. 7. 4	4. 0. 5
7. 6.10	11. 0. 3	11. 0. 3
5.12. 2	8. 8. 3	8. 8. 3
17. 4	1. 6. 0	1.11. 1
1. 1. 7	1.12. 4	1.18. 8
2. 8	4. 0	4. 9
3. 5	5. 2	6. 2
2. 8	4. 0	4. 9
3. 5	5. 2	6. 2
9. 6	14. 2	16.11
2. 8	4. 0	4. 9

SUNDRY ACCESSORIES (Contd.)

Auto couple release rod	9. 6	14. 2	16.11
Rewind crank for Kine EXAKTA	5. 3	7.10	9. 4
7 inch cable release for Varex	2. 8	4. 0	4. 9
7 inch cable release for Exa.	3. 5	5. 2	6. 2

FILTERS

32mm	15. 6	1. 3. 3	1. 7. 9
37mm	18.11	1. 8. 5	1.13.11
42mm	1. 1. 7	1.12. 4	1.18. 8
51mm	1.11. 0	2. 5. 6	2.15. 9
57mm	1.18.11	2.18. 4	3. 9. 8
49mm screw in	2. 0. 6	3. 0. 9	3.12. 7

All slip-on unless otherwise stated.  
Available in light, medium, and dark  
yellow, light and dark green, red, orange,  
ultra-violet.

Polarising Filter

51mm screw-in with case	8. 3.11	12. 5.11	14.13.11
-------------------------	---------	----------	----------